

Exceptional Value in an Advanced , Fully Featured IP Telephone

The Aastra 9143i (33i) offers advanced features and security in a standards based, carrier-grade IP telephone. Utilizing the very popular Aastra 9133i design, this powerful phone supports the advanced software features and interoperability previously available only with the Aastra 5i Series products. Equipped with a 3 line adjustable backlit display screen, full-duplex speakerphone, group paging, support for up to 9 calls simultaneously and XML browser capability, the 9143i (33i) will appeal to those requiring advanced SIP features in a traditional phone design.

Part of the Aastra IP Series of telephones, the 9143i (33i) is ideally suited as an everyday desk phone for moderate telephone users.



Key Features and Benefits:

» XML Browser

The Aastra 9143i (33i) is equipped with XML browser capabilities and a 3 line display with context sensitive keys to easily access customized services and applications. Create internal service applications using development guides available from Aastra. This feature provides unlimited potential to customize the 9143i (33i) to meet your specific business needs or vertical applications using the display and keypad.

» Enhanced Call Management

With extensive storage capacity for personal directories, callers logs and redial lists and 7 programmable keys, the Aastra 9143i (33i) can improve efficiency by providing more call information with the push of a button. Features such as shared call and bridged line appearances, call forward, call transfer, call waiting, intercom, group paging and local 3-way conference increase call flexibility and control.

» Remarkable Audio

All Aastra IP telephones offer full-duplex speakerphone with excellent voice clarity and delivery. With years of experience in telecommunications and telephone design, Aastra can ensure superior voice quality on every product we sell.

» Simplified Deployment

From initial deployment and configuration to future enhancements and upgrades, the Aastra family of IP telephones are designed to save your business time and money. Dual auto-sensing switched Ethernet ports eliminate additional wiring and simplify installations. Integrated IEEE 802.3af Power-over-Ethernet allows easy deployment with centralized powering and backup. Easily created configuration files, using any text editor, can be used to configure phones individually or centrally.

Feature Highlights*

- » Multi-proxy support
- » Distinctive ringing, priority alerting
- » XML browser
- » Personal directory
- » Call forward/Call transfer/Call waiting
- » Call timer
- » Caller and calling line information
- » Callers log
- » Local 3-way Conference
- » Intercom with auto-answer
- » Paging and auto-answer capabilities
- » Redial list
- » Do Not Disturb
- » Live dial pad support
- » Missed Call Notification
- » One-touch call transfer and call park
- » Busy Lamp Field (BLF)
- » Shared call and bridged line appearances
- » Broadsoft's BroadWorks Enhanced SIP – supports Shared Call Appearances, CommPilot Call Manager, Call Park/Pickup, Priority Alerting
- » Sylanro's SIP- supports Bridged Line appearances (BLA), ComCierge, Call Park/Pickup, Conference, SIP-B, and others

[†] Due to global numbering nomenclatures, branding on initial product shipments may reflect 3x model names

* Feature availability dependant on IP telephony systems

Feature Keys

- » Up to 9 lines with call appearances
- » 3 line/call appearance buttons with LEDs
- » 4 navigational keys
- » 7 programmable buttons with LEDs
- » 2 volume control keys
- » 10 dedicated hard keys including Conference, Call Transfer, Redial, Options, Directory, Callers, Save, Delete, Speaker/Headset, Mute

Audio and Codecs

- » Hearing aid compatible (HAC) handset
- » Full-duplex quality speakerphone
- » Independent volume setting for handset/speaker/headset
- » Echo cancellation
- » Comfort noise
- » Packet loss concealment
- » G.711 μ -law / A-law
- » G.729
- » Modular Headset Connector with built-in amplifier
- » Non-amplified business headsets recommended

Display and Indicator

- » 3 line adjustable backlit LCD display
- » LED for call and message waiting indicator

Security*

- » User and administrator level passwords for login
- » Encryption of configuration files
- » HTTPS configuration download and web management
- » Phone lock with PIN
- » Digest Authentication
- » Transport layer Security (TLS)
- » Secure Real-Time Protocol (SRTP)

XML API Capabilities

- » Display control based on user actions or on events
- » Dynamic Phone Configuration
- » RTP Streaming control
- » CTI applications
- » See XML API Documentation for more details

Interoperability

- » Visit www.aastratelecom.com for an up to date listing of approved vendor/interoperability

Localization

- » Multi-lingual support – English, French, Spanish, Italian, German
 - Downloadable language pack support for customization and additional language translations
- » Country-specific call progress tones and cadences

Protocols

- » IETF SIP (RFC3261) and associated RFCs

Networking and Provisioning

- » Dual 10/100 Mbps switched Ethernet ports
- » Manual or Dynamic Host Configuration Protocol (DHCP) IP address setup
- » Support of DHCP options 66, 60 & 43
- » Time and date synchronization using SNTP
- » Quality of Service (QoS) support – IEEE 802.1 p/Q VLAN and priority tagging, Type of Services (TOS), and Differentiated Services Code Point
- » Network Address Translation (NAT) support
- » Integrated HTTP/HTTPS server for web administration and maintenance including a built-in troubleshooting section
- » Mass deployment via central provisioning of user configuration files – TFTP, FTP, HTTP, HTTPS
- » Redundant server support
 - DNS-SRV
 - Local backup registrar and/or proxy server
- » RTCP support (RFC1889)
- » RTP streaming for Paging and Intercom applications
- » IEEE 802.1x protocol support

Power

- » AC wall adapter (48V DC) included
- » Integrated IEEE 802.3af Power Over Ethernet (PoE) support

Package Contents

- » Aastra 9143i phone
- » Handset coil cord
- » AC adapter
- » Desk Stand
- » Ethernet cable
- » Installation Guide
- » Key Card and Plastic Lens



Physical

- » 20.2 cm W x 19.5 cm D x 8.0 cm H (8.0" W x 7.7" D x 3.2" H)
- » 842 g (29.7 oz)
- » Wall mountable

Operating Conditions

- » Temperature: 0°C to 50°C (32°F to 122°F)
- » Relative Humidity: 20% to 90%, non-condensing
- » Storage Temperature: -50°C to 70°C (-58°F to 158°F)

Regulatory

CE /Europe

- » ROHS compliant
- » WEEE (2002/96/EC)
- » CE Mark (89/336/EEC EMC Directive and 73/23/EEC Low Voltage Directive)

EMC

- » FCC Part 15 Class B
- » ICES-003 Class B
- » AS/NZS 3548 Class B
- » EN55022 Class B
- » CISPR22 Class B
- » EN55024
- » EN61000 4-2, 4-3, 4-4, 4-5, 4-6, 4-8, 4-11

Safety

- » CAN/CSA C22.2 No. 60950
- » EN 60950
- » UL 60950-1

Telecom

- » FCC Part 68 (Hearing Aid Compatibility)
- » AS/NZS S004

Part Numbers

- » A1733-0131-10-05 9143i North America

* Feature availability dependant on the IP Telephony System

Rev 05/08